Submittal Data



BALL VALVE WITH HIGH-FLOW DRAIN

Job Name:	Submitted by:	Date:
Location:	Approved by:	Date:
Engineer:	Order No.:	Date:
Contractor:	Notes:	
Sales Ren ·		


DESCRIPTION


Ball valve with high-flow drain from Calefactio simplifies draining and maintenance for plumbing systems.

Its compact design reduces installation time and potential leak points, offering an efficient all-in-one solution.

TECHNICAL SPECIFICATIONS

- Full port brass valve
- High-flow drain
- Reversible handle
- Seat: PTFE
- ► O-ring: EPDM
- ▶ Connection: Sweat or Press, ¾″ to 1 ½″
- ▶ Pressure rating: 250 CWP





SWEAT

Model# Connection	Commontion	A		В		С		D		E		Weight	
	in	cm	in	cm	in	cm	in	cm	in	cm	lb	kg	
BD075S	3/4″	3.7	9.5	1.9	4.9	0.9	2.2	3.8	9.7	2.7	6.8	1.0	0.4
BD100S	1″	4.3	11.0	2.3	5.9	1.1	2.9	4.1	10.5	2.9	7.4	1.3	0.6
BD125S	1 1⁄4″	5.1	13.0	2.7	6.9	1.4	3.5	4.6	11.7	3.1	7.9	2.0	0.9
BD150S	1 1⁄2″	5.1	13.0	3.0	7.5	1.6	4.1	5.2	13.1	3.3	8.4	2.9	1.3

PRESS

Model# Connection	Commention	А		В		С		D		E		Weight	
		in	cm	in	cm	in	cm	in	cm	in	cm	lb	kg
BD075P	3⁄4″	3.7	9.5	1.9	4.9	0.9	2.3	2.8	7.1	2.7	6.8	1.0	0.5
BD100P	1″	4.3	11.0	2.3	5.9	1.1	2.9	3.3	8.5	2.9	7.4	1.4	0.6
BD125P	1¼″	5.1	13.0	2.7	6.9	1.4	3.5	3.9	9.8	3.1	7.9	2.1	1.0
BD150P	1 1/2″	5.1	13.0	3.0	7.5	1.7	4.2	4.4	11.2	3.3	8.4	2.9	1.3

TYPICAL SPECIFICATIONS

Furnish and install as shown on plans and descibed as follow a Calefactio ball valve with high-flow drain with a ______ in connection. The ball valve must be Calefactio's model BD______ or approved equivalent.